

Superwinch LP10000

10000 lb (4500kg) 12 volt recovery 4wd Winch



Specifications

| | |
|------------------------------|---|
| Rated Line Pull | 10,000 lbs (4,536 kgs) |
| Motor | 5.1 HP, Series Wound |
| Gearing | 3-Stage Planetary |
| Gear Ratio | 235:01:00 |
| Solenoid | Weather-Sealed Solenoid and Circuit Breaker Protected |
| Clutch | Free-Spooling, Lever Shift |
| Brake | Mechanical, Automatic Load Holding |
| Rope | Wire Rope 3/8" x 85' (9.5mm x 25.9m) |
| Hook | Clevis Hook with Latch |
| Fairlead | Heavy Duty, 4-Way Roller |
| Remote | Rubber 12' Hand-held |
| Dimensions | 21.3" L x 6.3" D x 8.6" H (541 mm L x 160 mm D x 218.4 mm H) |
| Drum Diameter | 2.5" (63.5mm) |
| Drum Length | 8.8" (224mm) |
| Mounting Bolt Pattern | 10" x 4.5" (254mm x 114.3mm) |
| Installed Weight | 83 lbs (37.64 kgs) |
| Shipping Weight | 90 lbs (40.8 kgs) |
| UPC | 0 22705 00341 4 |
| Line Pull: 0 lbs | 90 Amps Motor Draw / 16.0 FPM (4.87 MPM) Line Speed |
| Line Pull: 10,000 lbs | 350 Amps Motor Draw / 1.52 FPM (0.46 MPM) Line Speed |