

SUPERWINCH

LT4000

4000 lb (1814 kg) 12 volt
Steel or Synthetic rope



Specifications		
Model	LT4000	LT4000SR
Part Number	1140220	1125230
Rated Line Pull	4,000 lbs (1814 kgs)	
Motor	Sealed 1.4 hp motor	
Gearing	3-Stage Planetary	
Gear Ratio	166:01:00	
Solenoid	Sealed Solenoid; Circuit Breaker Protected	
Clutch	Free Spooling, Ergonomic Control	
Brake	Automatic, 100% Load Holding	
Rope	Wire Rope 50' x 3/16"	Synthetic Rope 50' x 3/16"
Hook	Heavy Duty Clevis Pinned Latched	
Fairlead	Heavy Duty 4-Way Roller	Aluminum Machined Hawse
Remote	12' Handheld plus Handle Bar Rocker Switch	
Dimensions	13.2"L x 4.25"W x 4.25"H (335.3mm L x 108mm W x 108mm H)	
Drum Diameter	2.0" (50.2mm)	
Drum Length	TBD	
Mounting Bolt Pattern	4.87" x 3.0"	
Installed Weight	Synthetic 22 lbs (10 kg) / Steel 25.6 lbs (11.6 kg)	
Shipping Weight	Synthetic 25 lbs (11.2 kg) / Steel 29 lbs (13 kg)	

PERFORMANCE



Max. Pulling Capacity	LOAD		SPEED		CURRENT DRAW
	lbs	kg	ft/min	m/m	*12VDC Motor Current, Amps
4,000 lbs (1814 kg)	0	0	20.0	6.0	20
	1,000	453	15.5	4.7	75
	2,000	907	12.0	3.6	110
	3,000	1360	9.0	2.7	160
	4,000	1814	5.5	1.6	220

* Performance based on first layer of rope wrapped on the drum

