

Superwinch S9000

Made in the USA



Load lbs	kg	Speed* 12V		Speed* 24V		Motor Current (Amps)*	
		ft/mln	m/mln	ft/mln	m/mln	12V	24V
0	0	38.2	11.6	38.0	11.6	73	42
1,000	454	18.0	5.5	21.7	6.6	130	72
2,000	907	13.8	4.2	17.1	5.2	165	90
4,000	1814	9.0	2.7	12.0	3.6	240	133
6,000	2722	6.0	1.8	8.3	2.5	316	181
9,000	4082	2.5	0.8	3.5	1.0	420	252

PERFORMANCE		
Wire Rope Layer	Max. Pulling Capacity lbs	kg
1	9,000	4082
2	7,365	3340
3	6,230	2825
4	5,400	2450
5	4,765	2161

Rated Line Pull	9,000 lbs (4,082 kgs)
Motor	4.2 hp Series Wound
Gearing	Planetary Differential
Gear Ratio	253:1
Solenoid	Double acting solenoid x two
Clutch	Free-Spooling Clutch - 1/4 Turn Activation
Brake	Automatic, 100% Full Load Holding
Rope	Wire Rope 5/16" x 100' (7.9mm x 30.5m)
Hook	Heavy Duty/Clevis Pinned/Latched
Fairlead	Heavy-Duty, 4-Way Roller
Remote	15' Sealed Hand-Held
Dimensions	(598mm L x 171mm D x 243mm H)
Drum Diameter	2.5" (64mm)
Drum Length	9.0" (229mm)
Mounting Bolt Pattern	10" x 4.5" (254mm x 114.3mm)
Installed Weight	84.0 lbs (38.1 kgs)
Shipping Weight	96.0 lbs (43.54 kgs)
Warranty	12 month manufacturers Warranty
UPC	0 22705 01917 0
Line Pull: 0 lbs	73 Amps Motor Draw / 38.2 FPM (11.6 MPM) Line Speed
Line Pull: 9,000 lbs	420 Amps Motor Draw / 2.5 FPM (0.8 MPM) Line Speed

