



1. Only Foot-Dow Mount winch available at these capacities.

2. Massive gears, Talon Large Chassis winches feature a monster gear set, over 45mm wide to promote positive engagement and long gear life.

3. Synthetic Rope Superwinch uses 1/2" certified Amsteel Blue Dyneema® rope for our large chassis Talon winches. Choosing synthetic rope can save as much as 25 lbs. over steel cable.

4. Limited Lifetime Warranty – Confidence on display – only Superwinch is bold enough to not only offer a Limited Lifetime Warranty, but also include an industry-leading 3 year electrical warranty.

No other manufacturer believes in their product like Superwinch.

Model	14	14SR	18	18SR
Part Number	1614200	1614201	1618200	1618201
Voltage	12 VDC	12 VDC	12 VDC	12 VDC
Rated Pull lbs (kg)	14,000 (6350)		18,000 (8165)	
Motor hp (kW)	5.2 (3.8)		6.0 (4.44)	
Gearing	2-Stage Spur/2-Stage Planetary			
Gear Ratio	346:1			
Solenoid	VS4 (Sealed Submersible Vented)			
Freespool	Ergonomic Pull and Turn			
Brake	Automatic, Load Holding, Located Outside Drum			
Rope Length ' (m)	90 (27.43)			
Rope Dia " (mm)	1/2 (13)			
Hook	Heavy Duty/Clevis Pinned/Latched, 14, 18 • Half Link Hook, 14SR, 18SR			
Fairlead/Hawse	Fairlead	Hawse	Fairlead	Hawse
Remote Control	Exclusive Ergo Handheld			
Installed lbs (kg)	170 (77.1)	145 (65.7)	172 (78)	147 (66)
Shipping lbs (kg)	183 (83)	158 (71.6)	185 (83.9)	160 (72.5)
Warranty	Limited Lifetime Plus 3-Year Electrical			
UPC	022705169127	022705169134	022705169141	022705169158
Performance	14	14SR	18	18SR
No Load Amps	75			
Line Speed FPM (MPM)	25 (7.62)			
At Load Amps	345		415	
Line Speed FPM (MPM)	4.25 (1.29)		2.5 (0.76)	
Alternate Versions	14	14SR	18	18SR
24VDC Versions:	1614300	1614301	1618300	1618301
No Rope 12VDC	1614202		1618202	
No Rope 24 VDC	1614302		1618302	

Mounting Bolt Pattern: 10" x 4.5" (254mm x 114.3mm) & 10" x 6.5" (254mm x 165.4mm)

