

# Terra Specifications



Model	25	25SR	35	35SR	45	45SR
Part Number	1125220	1125230	1135220	1135230	1145220	1145230
Voltage	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC
Rated Pull lbs (kg)	2500 (1134)		3500 (1588)		4500 (2041)	
Motor hp (kW)	1.3 (.96)		1.6 (1.2)			
Gearing	3-Stage Planetary					
Gear Ratio	140:1			191:1		
Solenoid	Sealed Solenoid with Circuit Breaker					
Freespool	Ergonomic Control					
Brake	Mechanical, Automatic, Load Holding					
Rope Length ' (m)	50 (15.2)				55 (16.8)	
Rope Dia " (mm)	3/16 (4.8)	3/16 (4.8)	13/64 (5.2)	3/16 (4.8)	1/4 (6.5)	
Hook	Heavy Duty/Clevis Pinned/Latched					
Fairlead/Hawse	Fairlead	Hawse	Fairlead	Hawse	Fairlead	Hawse
Remote Control	10' Rugged Handheld and Handbar Switch					
Weight Installed lbs (kg)	18 (8.2)	15 (6.8)	20 (9.1)	17 (7.7)	22 (10)	19 (8.6)
Weight Shipping lbs (kg)	29.5 (13.3)	23.7 (10.7)	30.9 (14.0)	25.2 (11.4)	34 (15.4)	27.9 (12.7)
Warranty	Limited Lifetime Warranty					
UPC	022705003421	022705003438	022705003445	022705003452	22705003469	22705003476
Performance	25	25SR	35	35SR	45	45SR
No Load						
Amps	25		19		21	
Line Speed fpm (mpm)	26 (7.9)		24 (7.3)		15.0 (4.6)	
At Load						
Amps	162		190		178	
Line Speed fpm (mpm)	10.5 (3.2)		10.2 (3.1)		5.5 (1.7)	

## Terra 2500 & 3500

## Terra 4500

